

Express Mail Label No. EL172582475

Docket No.: END9-2000-0111 US1

NEW UTILITY PATENT APPLICATION TRANSMITTAL**(Large Entity)***(Only for new nonprovisional applications under 37 CFR 1.53(b))*

Total Pages this Submission:3

TO THE ASSISTANT COMMISSIONER FOR PATENTSBox Patent Application
Washington, D.C. 20231

Transmitted herewith for filing under 35 U.S.C. 111(a) and 37 C.F.R. 1.53(b) is a new utility patent application for an invention entitled:
System and Method for Providing an Application Navigator Client Menu Side Bar

and invented by:
 STANLEY P. CASON

If a **CONTINUATION APPLICATION**, check the appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part(CIP) of prior application
 No.: _____

Enclosed are:

Application Elements

01. ☒ Filing fee as calculated and transmitted as described below
02. ☒ Specification having 86 pages and including the following:
 - a. ☒ Descriptive Title of the Invention
 - b. ☒ Cross References to Related Applications (if applicable)
 - c. ☐ Statement Regarding Federally-sponsored Research/Development (if applicable)
 - d. ☐ Reference to Microfiche Appendix (if applicable)
 - e. ☒ Background of the Invention
 - f. ☒ Brief Summary of the Invention
 - g. ☒ Brief Description of the Drawings (if drawings filed)
 - h. ☒ Detailed Description
 - i. ☒ Claim(s) as Classified Below
 - j. ☒ Abstract of the Disclosure
03. ☒ Drawing(s) when necessary as prescribed by 35 USC 113)
 - a. ☐ Formal
 - b. ☐ Informal

Number of sheets: 20

09/07/00

JC678 U.S. PTO

JC675 U.S. PTO

09/657195

09/07/00

09657195-090700

NEW UTILITY PATENT APPLICATION TRANSMITTAL**(Large Entity)***(Only for new nonprovisional applications under 37 CFR 1.53(b))*

Total Pages this Submission:3

Application Elements (Continued)04. ☒ Oath or Declaration

- a. ☒ Newly executed (original or copy) ☐ Not executed
- b. ☐ Copy from a prior application (37 CFR 1.63(d)) *(for continuation/divisional application only)*
- c. ☒ With Power of Attorney ☐ Without Power of Attorney

05. ☐ Incorporation By Reference *(usable if box 4b is checked)*

The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Item 4b, is considered as being part of the disclosure of accompanying application and is hereby incorporated by reference therein.

06. ☐ Computer Program in Microfiche *(Appendix)*07. ☐ Nucleotide and/or Amino Acid Sequence Submission *(if applicable, all must be included)*

- a. ☐ Paper Copy
- b. ☐ Computer Readable Copy *(identical to computer copy)*
- c. ☐ Statement Verifying Identical Paper and Computer Readable Copy

Accompanying Application Parts08. ☒ Assignment Papers *(cover sheet & document(s))*09. ☐ 37 CFR 3.73(B) Statement *(when there is an assignee)*10. ☐ English Translation Document *(if applicable)*11. ☐ Information Disclosure Statement/PTO-1449 ☐ Copies of IDS citation12. ☐ Preliminary Amendment13. ☒ Acknowledgment postcard14. ☒ Certificate of Mailing

☐ First Class ☒ Express Mail (Label No: EL172582475)

15. ☐ Certified Copy of Priority Document(s) *(if foreign priority is claimed)*

NEW UTILITY PATENT APPLICATION TRANSMITTAL**(Large Entity)***(Only for new nonprovisional applications under 37 CFR 1.53(b))*

Total Pages this Submission:3

Accompanying Application Parts (Continued)16. ☐ Additional Enclosures (identify below)**Fee Calculation and Transmittal****CLAIMS AS FILED**

For	# Filed	# Allowed	# Extra	Rate	Fee
Total Claims	9	-20	0	x \$18.00	\$
Indep. Claims	6	- 3	3	x \$78.00	\$ 234.00
Multiple Dependent Claims	_____				\$
BASIC FEE					\$ 690.00
Other FEE (Specify purpose)					\$
TOTAL FILING FEE					\$ 924.00

- ☐ A check in the amount of \$ _____ to cover the filing fee is enclosed.
- ☒ The Commissioner is hereby authorized to charge and credit IBM Corporation Deposit Account No. 09-0457 as described below. A duplicate copy of this sheet is enclosed.
- ☒ Charge the amount of \$924.00 as filing fee.
- ☒ Credit any overpayment.
- ☒ Charge any additional filing fees as required under 37 C.F.R. 1.16 and 1.17.
- ☐ Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b).

Dated:

31 Aug 2000


Signature

 Shelley M Beckstrand
 Reg. No. 24,886

 314 Main Street
 Owego, NY 13827-1616
 Phone: (607) 687-9913

cc:

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of: S. P. Cason
Serial No.: N/A Group No.: N/A
Filed: Herewith Examiner: N/A
For: System and Method for Providing an Application Navigator Client Menu Side Bar

Assistant Commissioner For Patents
Washington, D.C. 20231

EXPRESS MAIL CERTIFICATE

"Express Mail" label number: EL172582475

Date of Deposit: 09/07/00


I hereby certify that the following attached paper or fee

New Utility Patent Application Transmittal
Specification: 86 pages (including claims)
Declaration and Power of Attorney
Drawings (20 sheets)
Assignment
Recordation Cover Sheet
Express Mail Certificate
Postcard

is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Georgia Y. Brundage

(Name of person mailing paper or fee)


(Signature of person mailing paper or fee)

NOTE: Each paper must have its own certificate and the "Express Mail" label number as a part thereof or attached thereto. When, as here, the certification is presented on a separate sheet, that sheet must (1) be signed and (2) fully identify and be securely attached to the paper or fee it accompanies. Identification should include the serial number and filing date of the application as well as the type of paper being filed, e.g., complete application, specification and drawings, responses to rejection or refusal, notice of appeal, etc. If the serial number of the application is not known, the identification should include at least the name of the inventor(s) and the title of the invention.

NOTE: The label number need not be placed on each page. It should, however, be placed on the first page of each separate document, such as, a new application, amendment, assignment, and transmittal letter for a fee, along with the certificate of mailing by "Express Mail". Although the label number may be on checks, such a practice is not required. In order not to deface formal drawings, it is suggested that the label number be placed on the back of each formal drawing or the drawings be accompanied by a set of informal drawings on which the label number is placed.

a:\cert\EXPRESSmail.wpd

Parameter	Unit	Value	Standard Error	t-Statistic	p-Value
Intercept		1.0000	0.0000	1.0000	0.0000
Age	Years	0.0000	0.0000	0.0000	0.0000
Gender		0.0000	0.0000	0.0000	0.0000
Married		0.0000	0.0000	0.0000	0.0000
Education	Years	0.0000	0.0000	0.0000	0.0000
Income	Logarithm	0.0000	0.0000	0.0000	0.0000
Health		0.0000	0.0000	0.0000	0.0000
Smoking		0.0000	0.0000	0.0000	0.0000
Alcohol		0.0000	0.0000	0.0000	0.0000
Exercise		0.0000	0.0000	0.0000	0.0000
Stress		0.0000	0.0000	0.0000	0.0000
Family Size		0.0000	0.0000	0.0000	0.0000
Work Hours		0.0000	0.0000	0.0000	0.0000
Unemployment		0.0000	0.0000	0.0000	0.0000
Health Insurance		0.0000	0.0000	0.0000	0.0000
Medication		0.0000	0.0000	0.0000	0.0000
Comorbidities		0.0000	0.0000	0.0000	0.0000
Genetics		0.0000	0.0000	0.0000	0.0000
Environment		0.0000	0.0000	0.0000	0.0000
Lifestyle		0.0000	0.0000	0.0000	0.0000
Psychological		0.0000	0.0000	0.0000	0.0000
Social Support		0.0000	0.0000	0.0000	0.0000
Healthcare Access		0.0000	0.0000	0.0000	0.0000
Healthcare Quality		0.0000	0.0000	0.0000	0.0000
Healthcare Cost		0.0000	0.0000	0.0000	0.0000
Healthcare Satisfaction		0.0000	0.0000	0.0000	0.0000
Healthcare Utilization		0.0000	0.0000	0.0000	0.0000
Healthcare Access Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Quality Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Cost Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Satisfaction Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Utilization Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Access Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Quality Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Cost Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Satisfaction Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Utilization Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Access Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Quality Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Cost Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Satisfaction Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Utilization Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Access Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Quality Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Cost Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Satisfaction Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Utilization Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Access Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Quality Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Cost Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Satisfaction Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Utilization Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Access Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Quality Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Cost Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Satisfaction Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Utilization Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Access Barrier		0.0000	0.0000	0.0000	0.0000
Healthcare Quality					

TITLE **System and Method for Providing an
Application Navigator Client Menu Side
Bar**

INTERNATIONAL BUSINESS MACHINES CORPORATION

I hereby certify that, on the date shown below, this correspondence is being deposited with the United States Postal Service in an envelope addressed to the Assistant Commissioner for Patents, Washington, D.C., 20231 as "Express Mail Post Office to Addressee" on 09/07/00

Name of person mailing paper: Georgia Y. Brundage

Signature _____ Date _____

**SYSTEM AND METHOD FOR PROVIDING AN APPLICATION NAVIGATOR
CLIENT MENU SIDE BAR**

Background of the Invention

Cross References to Related Applications

5 The following U.S. patent applications filed
concurrently herewith are assigned to the same assignee
hereof and contain subject matter related, in certain
respects, to the subject matter of the present application,
the teachings of which applications are incorporated herein
10 by this reference:

Serial No. 09/_____, entitled "System and Method for
Clustering Servers for Performance and Load Balancing",
assignee docket END9-2000-0104-US1;

15 Serial No. 09/_____, entitled "System and Method for Front
End Business Logic and Validation", assignee docket END9-
2000-0105-US1;

Serial No. 09/_____, entitled "System and Method for Data
Transfer With Respect to External Applications", assignee

docket END9-2000-0106-US1;

Serial No. 09/_____, entitled "System and Method for Providing a Relational Database Backend", assignee docket END9-2000-0107-US1;

- 5 Serial No. 09/_____, entitled "System and Method for Providing a Role Table GUI via Company Group", assignee docket END9-2000-0108-US1;

- 10 Serial No. 09/_____, entitled "System and Method for Populating HTML Forms Using Relational Database Agents", assignee docket END9-2000-0109-US1;

Serial No. 09/_____, entitled "System and Method for Catalog Administration Using Supplier Provided Flat Files", assignee docket END9-2000-0110-US1.

Technical Field of the Invention

- 15 This invention pertains to a system and method for managing a requisition catalog on the web.

Background Art

A requisition catalog for a large enterprise in a web environment must enable very fast access to a very large database from a large number of clients. A large number of clients is required for optimal performance of a catalog system. There is a need to architect such a system so as to be scalable, that is, capable of providing that fast access to an ever increasing number of clients and a growing database or collection of databases.

In a requisition catalog system for a large enterprise in a web environment, there is a requirement for a system and method for insuring that all general ledger accounts associated with commodities are correct, and within this requirement for providing a description from the associated accounting system for use by customer or requester to select the correct general ledger (GL) account when doing financial validation on a requisition.

A requisition catalog for a large enterprise is stored in a very large database. However, a Lotus Notes database has a hard limit of 2 to 4 gigabytes of data. That is, Notes puts its entire database into one big Notes standard format(.nsf) file. Information in such a .nsf file is accessed by a system geometrically. As a result, such a system slows down significantly as it accesses larger files.

This slow down ramps up rather badly. Consequently, the hard limit is artificially put in because of this ramp up in access time. The typical solution to this problem is to split a very large database into many smaller databases.

5 Lotus Notes has a Lotus connector/Lotus script extensions connector (LCLSX). This allows connection to other databases but these script extensions are not set up to actually be the database. There is a need in the art for a system and method for utilizing Lotus script extensions in
10 combination with a relational database to provide high capacity storage without performance degradation.

In building a requisition catalog for a large enterprise with many suppliers, an automated process is needed to receive a flat file from a supplier for review by
15 a buyer before being externalized for use by requesters. While the buyer must be able to review the contents, he must be restricted from making changes to certain sensitive fields, such as changing a unit price or a unit of measure, both of which could constitute fraud. Consequently,
20 allowing the buyer to edit the flat file can't provide the level of security required. There is a need in the art to provide a buyer a means of auditing catalog content before externalizing it to production for access by requesters.

connecting to DB2 and reading data from DB2 tables. No
function is provided in Java script and in HTML to connect
to or access such a database. It is not presently possible
to make the connection by connecting to the database and
5 executing SQL queries. Consequently, there is a need in the
art for a system and method utilizing an existing
infrastructure including Lotus Notes, Domino Go, and DB2 to
combine HTML and Java script web presentation with DB2 data.

10 In a requisition catalog system for use in a web
environment by a large enterprise, there must be provide a
way to deal with web sites that exist outside of a firewall,
or internal applications within the firewall but outside of
the requisition catalog (Req/Cat Web or RCW) application.
That is, a system and method is required for transferring a
15 large quantity of data back from such a web site or
application to the RCW application in a timely manner. One
possible way is to send data on the universal resource
locator (URL). However, such a URL is limited to 1K bytes,
which is not enough to do the task quickly for the
20 quantities of information required. Information can be put
into a frame, and that information can be read, but only if
the information is written and read by the same server.

In a preferred system, the RCW application exists in a

END9 2000 0111 US1 6

frame set in a browser. As part of security for such a browser, Netscape and Internet Explorer (IE) establish ownership of the frames: each frame is a window under control of the browser. A user can open up a session in any frame desired. However, if all of the frames are not owned by same session, then these frames not commonly owned cannot see the contents of each other. In Netscape version 4.51 frame ownership was changed to protect against frame spoofing. Frame spoofing is a way other servers can use to trick the owner of a frame into thinking it had created a frame actually created by someone else, enabling access to data not owned. Netscape 4.51 plugs that hole.

Consequently, in the new environment (with spoofing inhibited) a problem is presented: if a RCW application needs to access an outside supplier site for information to get back through one its own the frames, as soon as data is written by that outside supplier site into one of the frames owned by RCW, ownership of the frame is transferred from RCW to the supplier; RCW no longer owns the frame and cannot access the information. A system and method is needed to enable transfer of data from a supplier site to a RCW application which does not entail frame spoofing.

In a web application, such as a requisition catalog

system for a large enterprise, a fast browser interface and navigator is needed, including a very fast graphical user interface (GUI).

There is known in the art several Internet applications which provide a strip down, for example, the left hand side of a window that has menu of items from which a user may select. Such windows also may display a header, including header type items which will expand upon selection into a drop down list. Such windows also may include a footer including leafs which will, upon selection, change what is seen on right side of screen. Such applications provide a very nice user interface for documents, with a table of contents (TOC) on the left, and on the right the selected contents.

However, these expandible and collapsible menus are characteristically slow. This slowness is a result of every click sending a request to a remote server, which server responds by sending information back to expand the list at the browser. Every click on the web is slow, involving communications of the request and response over a relatively slow web communication link. There is, therefore, a need in the art to dramatically increase the speed of operation of a graphical user interface at a browser.

It is an object of the invention to provide a scalable database system in a web environment with optimal access performance characteristics for an expanding number of clients and a growing database.

It is an object of the invention to provide a system and method for enabling a requester to select the correct general ledger account when doing financial validation on a requisition.

It is an object of the invention to provide a system and method for utilizing Lotus script extensions in combination with a relational database to provide high capacity storage without performance degradation.

It is an object of the invention to provide a system and method for enabling a buyer a means for editing catalog content before externalizing it to production for access by requesters.

It is an object of the invention to provide a system and method for providing very flexible access to DB2 tables without requiring database administrator (DBA) involvement to issue grants against the tables, and bypassing the

problem caused by Notes agents all coming from the same user
(the Notes server ID).

It is an object of the invention to provide a system
and method utilizing an existing infrastructure including
5 Lotus Notes, Domino Go, and DB2 to combine HTML and Java
script web presentation with DB2 data.

It is an object of the invention to provide a system
and method for enabling transfer of data from a supplier
site to a RCW application which does not entail frame
10 spoofing.

It is an object of the invention to provide a system
and method for dramatically increasing the speed of
operation of a navigation frame of a GUI.

Summary of the Invention

15 A system and method for presenting a browser navigation
frame. A screen display includes a customizable side bar.
Dynamic HTML is used by a navigator responsive to user input
to change data presented at the navigation frame without
having to communicate with a remote server.

Other features and advantages of this invention will become apparent from the following detailed description of the presently preferred embodiment of the invention, taken in conjunction with the accompanying drawings.

5

Brief Description of the Drawings

Figure 1 is a high level system diagram illustrating a clustered configuration of servers for performance and load balancing.

10

Figure 2 is a diagram illustrating proxying out of URLs to clustered servers.

Figure 3 is a system diagram illustrating a specific example of a clustered configuration of servers.

Figure 4 is a diagram illustrating the frames comprising a typical screen display.

15

Figure 5 is a diagram illustrating a specific instance of the display of Figure 4.

Figure 6 is a diagram illustrating ZIP code validation.

Figure 7 is a diagram illustrating requisition catalog searching.

Figure 8 is a diagram illustrating the mapping of
5 commodity codes to accounting codes.

Figure 9 is a diagram illustrating a commodity document.

Figure 10 is a diagram illustrating a pyramid structure of application program interfaces.

10 Figure 11 is a diagram illustrating the graphical, database, and business logic API's of the pyramid structure of Figure 10.

Figure 12 is a diagram illustrating the interaction of API's with each other, a database, and a browser.

15 Figure 13 is a diagram illustrating an example configuration of API's.

Figure 14 is a flow diagram illustrating the operation

of the userProfile class of Figure 13.

Figure 15 is a system diagram illustrating the system of Figure 1 for accessing a requisition catalog.

5 Figure 16 is a system diagram illustrating a system for using a staged requisition catalog built from supplier flat catalog files.

Figure 17 is a flow diagram illustrating the steps for receiving a supplier flat catalog.

10 Figure 18 is a flow diagram illustrating the steps executed by an application server and database server for building and accessing a requisition catalog.

Figure 19 is a diagram illustrating a user profile.

Figure 20 is a diagram illustrating a Notes agent for building an HTML page from a DB2 table.

15 Figure 21 is a diagram illustrating Notes agents for transferring data to an application browser session from a supplier window.

Best Mode for Carrying Out the Invention

1. Clustered Servers

In accordance with the preferred embodiment of the invention, a requisition catalog system (RCW, or Rec/Cat Web) is provided within a global web architecture (GWA) infrastructure. Such an architecture provides for the large number of clients required to assure good performance. In an exemplary embodiment, the requisition catalog application is deployed within the IBM web domain, which requires the use of GWA for clustering of W3 and www.ibm.com web sites. This architected solution assures a scalable Req/Cat Web application.

Referring to Figure 1, client browsers 100 are connected to a GWA infrastructure including network dispatcher 102 and domino.go, a virtual cluster of Domino servers. Network dispatcher 102, sprays out or dispatches requests among configured servers S1, S2, S3 in virtual server cluster 104. Communications from cluster 104 are, in turn, dispatched (also referred to as sprayed out,

distributed, proxy passed, or redirected) by network
dispatcher 106 among servers S4, S5, and S6 in Domino
cluster 112. While three servers are illustrated as
configured in each of clusters 104 and 112, each cluster
5 configuration may be scaled to any number of servers.

External objects 108, which can be stored on a distributed
file system (.dfs), include graphic files, Java files, HTML
images, net.data macros, and other .nsf files external to
Domino, and in particular include configuration file proxy
10 statements 110. In this instance, external objects 108 are
stored on a .dfs and exist only once, so it is not necessary
to replicate all of the external objects to each of the
servers S4-S6. External objects 108, served in a .dfs are
graphic files, Java files, anything that would live outside
15 of the server files (also referred to .nsf files) S4-S6,
including HTML images and net.data macros. These are part
of the code implementing the Req/Cat Web application of the
preferred embodiment of the invention, but are not part of
Domino code, and are primarily for the GUI. By storing them
20 outside of cluster servers 112, performance is improved.

In order to avoid potential bottlenecks on the
clustered Domino servers 112 and in order to store a larger
amount of data than is quickly searchable in Domino, a
relational database 129, such as the IBM DB2 database, is

.nsf files. Periodically, these servers replicate back and forth so that information is contained in all of them. Data is kept consistent.

In operation, when a client comes in through browser
5 100, his request can be directed to any domino.go server S1-S3 that determines the mapping of the URL request and what type of function is needed (displaying of images or code execution on S1-S3, or connecting to an .nsf server S4-S6 to display user data).

10 .nsf servers S4-S6 then feed requests to the application server 114, which in this embodiment is a backend Req/Cat Web (RCW) server to which all data gets replicated and where the bridges and agents run. Data gets replicated out to other back-end servers (DB2, MVS, SAP) 116
15 as needed. A bridge is an application that transfers data from one server to another server. An agent is an application that runs scheduled or by request to do some processing of data.

In an exemplary embodiment, Domino.go, or virtual
20 server cluster, 104 is part of the GWA infrastructure. Any w3.ibm.com or www.ibm.com must go through a domino.go cluster 104. In accordance with the present invention a

proxy out to the Domino cluster 112 is also provided. The purpose of this is to improve scalability and performance. Proxy statements 110 are used to ensure that the proper pieces of the application are invoked as appropriate, depending upon what the end user is doing. These statements are a mapping through a configuration file of URL 120 to any clustered server 112.

Referring to Figure 3, a specific exemplary embodiment of the invention includes client browser 100 connected to network dispatcher (URL redirect) 102, which is connected to GWA shared GO cluster (W3-1.IBM.COM) 104. Cluster 104 is connected to external objects including OBI 117 and DFS 118, to dedicated DB2 server 129, and to network dispatcher (proxy) 106. Dispatcher 106 is connected to dedicated Domino "end user" cluster 112. Cluster 112 is connected to Blue Pages database 121 (an internal personnel database), dedicated DB2 server 129, dedicated Domino "application" server 114, and other Notes databases 119, including Skills Matching (an application for contracting technical services), AMNF (an application for identifying nonmanager requisition approvers), and public address book (PAB, for user login and authentication). Application server 114 is connected to FormWave 125 (an application that does approval form routing), PRISM/Copics 123 (which are requisition

feeder systems on MVS and AS/400), SAP 382 (an ERP, or
enterprise resource planning system, including an accounting
application having an accounts payable function), dedicated
content staging server 127 where an administration Notes
5 client 128 runs, and dedicated DB2 server 129. The content
staging server is used to update both .nsf and DB2
configuration data, and is also connected to server 129.

004060 EST 030600
10 The architecture of Figure 3 presents a complex,
scalable global procurement application (referred to as
Req/Cat Web) implemented within Global Web Architecture
(GWA). Req/Cat Web allows customers to generate on-line,
general procurement requisitions. Customers interfacing
client browser 100 can search through vendor catalogs to
select items and fill in order information. Submitted
15 requisitions are routed through an approval process using
FormWave 125. Requisitions that have been approved are sent
to a back-end system (SAP) 382, where a purchase order is
cut and billing occurs. Customers can monitor their
requisition status, as the back end sends status updates to
20 the application 114.

Technologies utilized in building Req/Cat Web include
the following: Domino.Go 104 provides a proxy passing
function and caching facility. Lotus Notes/Domino is used

for its security and workflow capabilities. DB2 provides rich relational database functions and data management. Net.Data is used for its catalog searching functionality.

Javascript is used for GUI presentation and data

5 verification. Req/Cat Web application code sits on DFS 118, on the Domino cluster servers 112, and on Domino application server 114.

Architectural elements include load balancing, file storage, end-user front end (which reside in the Domino cluster servers 112), back-end processing, external dependencies, and use of frames.

For load balancing, Req/Cat Web uses the GWA proxy pass architecture, documented in the presentation currently available on the Notes/Web application CoC Web site at
15 <http://w3.coc.ibm.com/coc/cocweb.nsf/Homepages/gwatrain.html>.

Network dispatchers 102, 106 are used between the client 100 and the Domino.Go cluster 104 and also between the Domino.Go cluster 104 and Domino cluster 112 to automatically balance the load of http requests among
20 servers S1-S3 and S4-S6. Configuration file (httpd.conf) 110 contains the proxy statements that are used for redirections. When a client 100 enters the url

(w3.ibm.com/transform/reqcat) and Network dispatcher 106 redirects the client to the appropriate server 112, the redirection is transparent to the client.

5 Workload is split between Domino.Go 104 and Domino 112 to improve performance.

10 File storage is provided by dynamic file system (.dfs, or DFS) 118, which contains javascript files (.js), html, images, and net.data macros. Domino servers 114 contain navigation, configuration, create requisition, open requisition, requisition invoice paid, requisition archive, cost center, confirmations, and help databases. DB2 server 129 contains tables including: confirmations, user profiles, zip codes, accounting data, commodity configuration data, buyer information, routing, and catalogs.

15 An end-user front end for Req/Cat Web uses Domino authentication to permit login to the application. The client uses his Lotus Notes ID and pre-set http password to "authenticate". When a client logs in at browser 100, the Domino servers 112 (S4-S6) are configured to check the name and password in public address book 119, which is a designated server within GNA. In a further exemplary embodiment, secure login function may be provided through

the implementation of digital certificates. Data is
retrieved from DB2 129 using LC:LSX calls via Notes agents,
or Net.Data. Net.Data is used for a catalog searching and
drill-down function. Java APIs are used for information
5 retrieval from BluePages 121.

As much processing as possible is performed
asynchronously on the back-end, application server 114.
Bridge jobs are scheduled on two levels: system level (CRON)
and notes level (Agents). Agents run periodically, say
10 hourly, to process requisitions and send them to SAP 382.
Other agents are scheduled off-peak, where ever possible.

External dependencies include FormWave for form
approval routing, BluePages for personal data for user
profile creation and approver changes, interfaces to Open
15 Buying on the Internet (OBI) server and skill matching
applications, and SAP for receiving requisitions for
purchase order (PO) creation and processing. Information
returned by SAP to Req/Cat Web includes requisition status,
PO/RFS status, PO history, negative confirmations, currency
20 codes, and configuration information.

By using frames, a large majority of preprocessing can
be performed dynamically, on the client, reducing the number

of trips back and forth to the server. This is a tremendous boost to performance. The web screen described hereafter is not the result of a Notes form, but rather of a dynamically generated HTML/javascript code produced by a

5 displayReqHeader() function. This function dynamically writes html and javascript code into the content frame of the application. The javascript function is coded in a displayreq.js file stored on the filesystem and loaded into a jsCode frame by a source (<script src= "../js/
10 displayreq.js">) command in a jscode.html file at the time when the initial frameset is loading. A displayReqHeader() function is called from several places in the application to redisplay the requisition information in the content frame. This screen is called any time a WebReq Lotus Notes form is
15 opened by an OpenForm command for a new requisition, or by an OpenDocument command when an existing document is opened. OpenForm occurs when the displayReqHeader() javascript function is called as the last part of an OnLoad event coded in the HTML-Attributes property of the WebReq form. Any
20 time an existing document is opened that was saved with Form-WebReq, the OnLoad event causes the displayReqHeader() javascript to be run to OpenDocument. Any time a content frame has been loaded with some other page during the processing of a requisition, and the user performs an action
25 to return to the requisition in process, the

displyReqHeader() javascript function is called directly.
This form reads the information stored in reData frame and
dynamically fills the content frame with this screen.

Referring to Figures 4 and 5, as will be more fully
described hereafter, a screen display includes header frame
470, navigation frame 472, footer frame 474, temporary data
frame 476, request data frame 478, and content frame 480.
The tempData frame 476 is used as a temporary holder for
information, and to direct calls dynamically, while keeping
the current data in the screen, and making the return data
available to the application.

Table 1 shows, for the exemplary embodiment of Figure
3, the software loaded on each of the servers used for the
Req/Cat Web application.

TABLE 1 SERVERS AND SOFTWARE

<u>Server Description</u>	<u>Software</u>
Domino.Go Servers S1-S3	AIX 4.3.2 Domino Go 4.6.2.6 with Denial of Service Fix Net.Data 2.0.8 DB2 CAE 5.2 DFS Client Java Runtime 1.1.6
Domino End-User Servers S4-S6	AIX 4.3.2

ZIP code validation is provided to assure that the tax department is provided the information needed implement the correct tax rules on purchase orders in SAP 382.

Chart of accounts validation includes the mapping of commodity codes to account codes. This is done to insure that all general ledger accounts associated with commodities are correct, and within this to insure that a description from SAP 382 is available for use by a customer to select correct general ledger (GL) account when doing financial validation on a requisition.

Referring to Figure 6, for ZIP code validation, when a purchaser access RCW, a user profile 130 is accessed. Profile 130 includes many defaults, one of which is delivery information (defaulted to all line items of requisition). One of the fields in profile 130 is ZIP code. When the purchaser enters his ZIP code, RCW searches ZIP code database 134, a database for ZIP codes which is fed periodically, say nightly, from the enterprise tax system 136. This same validation routine continues by creating a requisition 132 with item options, including deliver to information with a zip code field. The requester can change the deliver to information, 132, but any time it is changed, the ZIP code is checked against ZIP code database 134.

Whereas previously, customer input of ZIP code was accepted without checking. By this invention, ZIP code validation is performed at the front end by a java or SQL program call to db2 database 134. Responsive to entry of ZIP code on a
5 requisition or to the changing of delivery information which includes ZIP code on a requisition line item, the ZIP code is validated against a database of valid ZIP codes. In an alternative embodiment, the ZIP code database is refreshed from a trusted source, and the entered or changed ZIP code
10 is checked for valid match with respect to state and city.

A create requisition request goes to catalog search, which used to search by part number or description. Previously, this was a very limited search to just the catalogs. A search argument of %pen% was not a very crisp
15 search for the customer. In order to improve the catalog search, in accordance with the present invention, searches may be conducted against a longer description and files up to 255 characters. Screen down searches are provided for sub-commodity. Wild card searches used to require %, but
20 now assumes a wild card search in all cases. Searches are also provided against subcommodity. As a result, catalog searches now reference short description, long description, and catalog sub-commodity. A database catalog includes part number, short description, long description, oem part

number, commodity code. Newly added is subcommodity.

Referring to Figures 7 and 9, the method of the preferred embodiment of the invention is described for managing a chart of accounts 140. When creating a commodity
5 list, which includes expense, capital, and resale accounts 142, commodities descriptions 180 are pushed to the correct commodity group. The resulting chart of accounts 140 is available from SAP 382. Previously an administrator had input a chart of accounts. Now, a company administrator,
10 for example, may select from commodity accounts 142 the expense field, which results in drop-down display of a valid chart of accounts 144 from SAP chart of accounts 140 with account numbers 148 and commodity descriptions 146. The company administrator may then select from that valid chart
15 of accounts 144 the correct commodity to push to company/commodity document 150.

Referring to Figure 8, the process for a requester to create requisition is set forth. By way of example, a requestor creates a requisition by doing in step 154 a
20 search for "supplies", which will bring to him in step 156 a display presenting commodity W14, and thence in step 158 to a catalog (for example, a Staples catalog) which includes commodities (pens, erasers, calendars), from which the

requester can create several line items. Upon selecting
"proceed to accounting", the requester is presented a
financial summary 160 including commodity code w14 pens for
line item 1, w14 erasers for line item 2, and w14 for line
5 item 3 calendars. The user may then request display of
financial worksheet 162. In this window 162, the requester
will see a title 164 expense, which can be changed, for
example, by toggling to other categories, such as balance
sheet. Selecting G/L account 166 may drop down a list
10 showing several account codes 168 and related descriptions
170, depending upon what the company administrator has
pushed to the commodity document 150 from which financial
worksheet 162 is derived. Previously, a requester was
provided in worksheet 162 one account code choice without
15 description. By this invention, the requester is provided
correct general ledger account codes and descriptions,
resulting in less miscodes, more correct ledger entries, and
correct SAP account codes. This improved general ledger
account selection process avoids back end processing to
20 correct erroneous entries.

Thus, in accordance with a preferred embodiment of the
invention, a method is provided for creating a valid chart
of accounts from which an administrator 184 can facilitate
and enable a requisitioner to select a valid general ledger

account. First, there is push from an enterprise (erp) system a chart of accounts 140 with descriptions to a req/cat system database. The administrator selects from req/cat system database valid accounts with descriptions for a given commodity and purchase time period, and then pushes the selected account/description tuple to the company commodity groups, thus completing the setup of the commodity documents 150 to be used in the requisition creation process. A company commodity document 150 created by administrator 184 may include for each commodity code under each company, commodity code 152, which is a very broad category, short description 190, long description 191 (from procurement organization 182), key words 192, approvers 193, financial information 194 (including purchase type 198, and general ledger account 199), route-to buyer 195 (by plant association), preferred supplier 196 (which associates the commodity code to a catalog 158), and special handling code 197 (with drop list including, for example, skills matching, obi, administrative services) -- all used to drive the customer to the correct commodity.

To create a requisition, a user searches against commodities and catalogs in commodity description documents 150, which may be Notes documents or DB2 records, and creates one or more line items. These searches may be done

by catalog and non-catalog, and driven based on descriptions entered by requester. A hierarchy of families may be provided as an alternative search approach. The requisitioner initiates a proceed to accounting process, which displays line items which may be selected by requisitioner; and then displays a financial worksheet created by a Java agent with fields which need to be selected or populated by the requisitioner from the company commodity document, based on purchase type, and which presents valid general ledger accounts numbers and descriptions to the requisitioner.

3. Back End

Referring to Figure 12, in a large enterprise, the requisition catalog requires a very large database. In accordance with the preferred embodiment of the invention, such a large data repository is provided by the using the IBM DB2 relational database 210. Other possible databases include Oracle, Sybase, and MSSQL.

Lotus Notes databases are built upon an object model and classes: databases, views, and documents are classes used to access Notes data. But, these classes are set to be

final and not extendible, and a Req/Cat Web database must be extendible.

Consequently, referring to Figure 12, in accordance with an embodiment of the present invention, DB2 access routines 208 are provided for accessing DB2 data 210. The Req/Cat Web application executes Lotus code, with access controlled on the code, and data obtained from and written to relational database 210.

Normally, Notes saves all data as documents. There is a save method provided for that purpose. In accordance with a preferred embodiment of the invention, the Notes save method is intercepted and stopped, and execution passed to Req/Cat Web code for saving data to DB2. In the same way, execution of a Notes open method is intercepted and stopped, and then Req/Cat Web code executed to pull information in from DB2.

Lotus Notes provides for web applications, and supports methods called webqueryopenagent, and webquerysaveagent. Notes also provides a saveoptions parameter. Setting saveoptions to zero tells Notes not to save a document.

In accordance with the preferred embodiment of the

invention, saveoptions is set to zero, and webquerysaveagent
used to save data in DB2. The webquerysaveagent is written
in Lotus Script, and calls Lotus Script extensions and also
can also call its own APIs 200, 202, including the database
5 api's 208. At this point, Req/Cat Web has full control,
and can save one or many tables, can explode the data model
and write many tables.

On the other side, instead of editing an existing
document as is done with Notes, Req/Cat Web executes
10 createnewdocument. As the document opens, Lotus Notes gives
the query webqueryopenagent, and this is also written in
Lotus Script, which has access to data base api's 202, where
data from many database 210 tables may be read to construct
a Lotus document from DB2.

15 This configuration involves some naming standards and a
hierarchy of interfaces. By way of example, database access
routines are, by convention, data application programming
interfaces (DAPI) 208. These are routines for accessing
data 210 outside of the Req/Cat Web application. Referring
20 to Figure 10, a hierarchy of application program interfaces
(APIs) includes core API's 200 containing everything
necessary to connect to database 210. Next in hierarchy, to
access specific data, are database API's (DAPI) 208, which

interface to a single piece of data (such as company or employee information.) Below these rest the business logic code 204.

In a programming environment, the top of pyramid represents the work of a core DB2 programmer. Below him are those people who use core DB2 API's and write, for example, DAPI's 208 to access individual DB2 tables within database 210, for example API's for countries. These core APIs 200, therefore, include a GET method, and update, insert, and delete routines. Third level 204 represents the application programmer who only needs to use these methods (ie, company dapi: IBM US) in their business logic 204 applications, including ability to update, for example.

Referring to Figure 11, this same pyramid is used to implement graphical APIs 206 on the user interface 212, business APIs 207 on the business logic 204 interface, and database APIs 208 on the database 210 interface. This illustrates that duties of programmers can be separated, so that everyone need not know the complexities of the entire system. That is, some developers work on data manipulation, others on the user interface, and still others on business logic. The application developer need not know the names of the actual database, tables, or fields, or even how to

access them. This also enables a DB2 administrator to alter a table, and only affect the one DAPI developer that wrote the specific table DAPI 202. All code is one routine, so changes to the database need only affect one piece of logic.

5 Referring to Figure 13, an example of this API implementation is illustrated. CoreDB2 220 is the core API 200 to connect to DB2 210. It contains two classes, configuration class DB2Config 222 and base class DB2Base 224.

10 Calling DB2Config 222 determines database name 230, user identifier 231, and password 232 - information that the database requires to establish a valid connection, and is passed to DAPI 208 for making that connection. (Without this method, user IDs and passwords would have to be hard
15 coded in the application.)

DB2Base 224 is extended by the DAPI 208 programmer for each DAPI 202 instance that is needed. It contains methods 240, 241 for connecting to and disconnecting from the database, a method 242 for defining the number of rows to
20 return at a time, a method 243 for getting the next group of records, methods for reads 244, inserts 245, updates 246, and deletes 247, commit 248 and rollback 249 options, and a

flag 250 to determine if all data has been retrieved.

DAPIUserProfile 226 is a class for retrieving or updating information about an employee. It extends DB2Base 224 so the application 204 developer would not have to write the logic to access DB2 210, but could concentrate on the information about the employee. The DAPI 202 developer would need to know about the employee table (table and field names, for example) and would implement methods for selecting and displaying data. In an exemplary embodiment, DAPIUserProfile class methods include the following:

```
260  selectEmployeeByEmpID(employeeID,companyCode,
      countryCode)
261  selectEmployeeByWebID(employeeWebID)
262  selectEmployeeBothWays(employeeID,companyCode,
      countryCode,employeeWebID)
263  selectEmployeeByName(lastName,firstName)
264  insertEmployee(columnNames,DB2ColumnValues)
265  updateEmployeeByEmpID(employeeID,
      employeeCompanyCode,employeeCountryCode,
      UpdateNameValues...)
266  updateEmployeeByWebID(employeeWebID,
      UpdateNameValues,UpdateByUserID)
267  deleteEmployeeByEmpID(employeeID,companyCode,
```

```

countryCode,UpdateByUserID)
268 deleteEmployeeByWebID(employeeWebID,
UpdateByUserID)
269 deleteEmployeesWhere(Condition, UpdateByUserID)
5 270 clearTable()

```

Once the data is selected, a few of the properties that are available for a given employee include empWebID, empLastName, empFirstName, empIntPhoneNum, empExtPhoneNum, empEmailID, empID, empCompanyCode, empCountryCode, and empCountryName.

An application 204 like the human resources (HR) application would then need to read HR data and insert it into the employee table if the employee did not exist, or update it if something changed, or delete it if the employee no longer exists. This application developer would then only have to know the methods and properties of the userProfile class 226 in order to write the application. An example of such an application is set forth in Table 2, with reference to the steps of Figure 14. This table sets forth the HR load routine, a batch program to read HR data from a flat file and insert it into the DB2 user profile table.

TABLE 2 EXAMPLE APPLICATION

```

1      'in the following step, instantiate a DB2 config
2      object, and call it db2; the database name 230, etc.,
3      is determined by instantiating the db2 config object,
4      as defined by the core programmers'

5      272: Dim db2 As New DB2Config(session)

6      'the database information is known, and can be passed
7      to the employee profile.'

8      274: Print "The target DB2 database alias is "&
9      db2.getDB2DatabaseName()

10     'All that must be done is to pass the DB2 class to the
11     userProfile.'

12     276: Dim eps As New userProfile(db2)

13     'Delete everything from the employee table to start the
14     bridge.'

15     278: If headerDivision = "" Then
16         Call eps.clearTable()
17     Else
18         Call eps.deleteEmployeesWhere("COGRP_CD= ""
19         &headerDivision &""")
20     End If

21     280: For count = 2 To records-1

22         'Read the next record and make sure that it can be
23         loaded without problems'

24         If ReadInputFile(inputFileNum, count, userid, al, cl
25         eps, cci) Then

26             Call eps.insertEmployee(DB2ColumnNames,
27             BuildDB2ColumnValues())
28             db2kAdditions = db2Additions+1

29         End If

30     Next...

```

In Table 3, a pseudo code example of use of the webquerysaveagent process is illustrated.

TABLE 3 WEQUERYSAVEAGENT EXAMPLE

```
1      Dimension db2 As New DB2Config(session)
2      Print "The target DB2 database alias is "&
3      db2.getDB2DatabaseName()
4      Dimension eps As New userProfile(db2)
5      execute process 260 to selectemployee by employee id
6      if employee does not exist, then
7          execute process 264 to insert employee
8          else if employee changed, then
9              execute process 265 to update employee
10         else (employee not changed) information to user
11         "employee not changed"
12         no save
13     endif
```

In the example of Table 3, an application programmer 204 is using a dapi written by programmers 202.

In this manner, the relational database 210 is used as

the data source, instead of a Notes database, in a way that
hides the complexities of DB2 database programming. That
is, in a fashion to similar Notes programming - the idea is
to allow a Notes programmer to use a familiar looking class
5 226 to load and save data.

4. Catalog Administration

In accordance with the preferred embodiment of the
invention, a requisition catalog administration function
provides control, audit, and publishing procedures for flat
10 files received from suppliers.

Referring to Figure 15, a system architecture for
implementing catalog administration includes a requester
browser 410, a buyer browser 412, with net.data connections
391 and 393 to a dedicated DB2 server and DB2 database 390
15 having a staging table 392 and a production table 394
through network dispatcher 102 and Go cluster 104. Go
cluster 104 is also connected through network dispatcher 106
and Domino cluster 112 to Domino application server 114.
A buyer 412 accesses staging table 392 via net.data
20 connection 391, and a requestor 410 accesses the production

394 table via net.data connection 393. This connection 391,
393 is implemented as a single path, and the requester and
buyer provided different levels of authority to access
different tables 392, 394 in DB2 390 over that same path.

5 Buyer 412 can change selected fields in the staging table
392 and can update production table 394 from staging table
392. Requester 410 can only view (not change) the
production table 394. The buyer at browser 412 is
controlled by a GUI which contains access control list (ACL)
10 control on fields, and edit authority for catalog access.

Referring to Figure 16, this architecture further
includes a catalog flat file 314, an application program 384
within application server 114, catalog administration
function 386, Req/Cat Web function 388, and WEB
15 communications 396 and 398 connecting a catalog
administration function with ACL control 400 and requester
402 to database 390.

In operation, catalog flat file 314 is received by
application server 114 through firewall 380 via EDI and
20 loaded into DB2 database 390 by application program 384.
Catalog administration function 386 specific users 400 audit
control over certain fields in staging table 392, and
publishes the catalog data to the live, or production,

system 394. Function 386 presents to buyer 400 a staging table 392 with a GUI front end, with selected fields enable and other fields not enabled to be personalized.

5 Catalog file 314 is a flat file containing catalog items in a column delimited format specified to supplier 300 by the enterprise.

10 Application server 114 manages database 390 containing staging table 392 and production table 394. A catalog file 314 comes to application server 114, which includes a program 384 for moving data from that flat file to staging table 392.

15 A buyer at terminal 400 accesses the staging table 392 on the web 396. He views catalog items and enters transactions with action button which transfers information from staging table 392 to production table 394. Production table 394 is referenced by req cat web 388, and staging table 392 is referenced by the catalog administration function 386 operated by the buyer 400. Typically, a buyer is member of procurement organization with responsibility for negotiating deals with suppliers. A requester 402
20 accesses production table 394 over web 398 to create and submit a requisition to SAP 382.

In accordance with the preferred embodiment of the invention, control over what buyer 400 can change is provided by a GUI in a process which loads a catalog 392 from a supplier into a production system 394.

5 Catalog files 314 come in from suppliers in an enterprise defined standard format, and the access to fields in that format is hard coded into the catalog administration function 386. Application server program 384 has error checking functions to assure validity of a catalog 314 from
10 a supplier 300. Buyer 400 accesses staging table 392 through a catalog administration function 386 which has hard coded into it the access controls on the various fields in the catalog format. Production table 394, which is accessed by the requester 402, is updated periodically (upon buyer
15 actuation) from the staging table 392.

 Implementation of the invention involves several code procedures: there is a program 384 which loads a file 314 that is received via EDI into a table 392 in DB2. There are routines 388 which allow a buyer 400 to browse certain
20 catalogs in the staging table 392 and change certain fields while being inhibited from changing others. And there are the routines 386 which take the approved catalog and migrate the data from the staging DB2 table 392 to the production

DB2 table 394.

Referring to Figure 17, a preferred embodiment of these processes are presented. In supplier system 300, supplier source data 310 is extracted and reformatted in step 312 to create catalog flat file 314 in the format specified by the enterprise. In step 316 that flat file is transmitted to the enterprise 302, as is represented by line 305, where it is accepted in step 320 into the enterprise EDI mailbox 322. In step 324, the data in the flat file in mailbox 322 is reformatted and put into generation data group (GDG) 328, a location for saving more than one file, so as to retain the last N iterations, and a archive entry made to processing log 326. In step 330, a delivery component executes to send data from GDG 328 to application server 114, as is represented by line 303, in the form of catalog flat file 340. In step 342, a delivery component receives the flat file and, as is represented by line 347, starts job scripts including MASSLOAD for reading the flat file and loading staging table 392, and as represented by line 345 alerts the buyer 352. As is represented by lines 311, 313 and 315, respectively, MASSLOAD 344 accesses database server 306 procedures catalog_s 360, product_s 362, and Req/Cat Web 364, and makes an archival entry to processing log 346.

Catalog_S 360 is the staging table 392 for the catalog profile, which provides for each catalog the supplier name, the start and end dates of catalog validity, the currency, and so forth.

5 Product_S 362 is the staging table 392 that holds the catalog parts, a listing by part number of price, description, and so forth.

10 Req/Cat Web validate procedure 364 is a Java stored procedure for performing the initial validation of data received in flat file 340.

 Front end 370 is a GUI used by the buyer, for example to update the catalog 366.

15 In operation, validation procedure 364 validates the format and identifies catalog changes to product_s 362, logging those changes in file 332. It then checks a flag in catalog 366, and if the flag is on invokes procedure 350 provided catalog_s 360 does not indicate any critical errors. Validate and load procedure 350 then moves the contents of product_s staging table 362 into the appropriate
20 production table 368, writing any errors to processing log 348. (In the event that procedure 364 does not call

procedure 350, then buyer 352 intervention is required via GUI 370.) After procedure 364 completes execution, it may either stop, or if catalog 366 has a flag set on and catalog_s staging table 360 indicates no critical errors, then procedure 364 will invoke validation and migration procedure 350. After validate procedure 364 completes, it has written to prod_message_s file 332, and the buyer may use GUI 370 to read messages from file 332 and make any desired changes to staging table 362. The buyer may also choose to reject the catalog and, via step 354, contact the supplier to restart the process. This occurs if there is an error in the unit prices, which is an example of information in the catalog which a buyer is not authorized to change on his own.

After the buyer has used GUI 370 to make the values in staging table 362 acceptable, he sets the flag in staging table 360 which allows migration procedure 350 to run to move data from staging table 362 into production table 368, a relational database, such as Net Commerce (NC) or IBM DB2.

5. Role Table GUI

A preferred embodiment of the invention provides through use of a role table in DB2 database 129 (Figure 3, or 390 in Figure 16) very flexible access to DB2 tables without requiring involvement by a database administrator (DBA) to issue grants against the tables, thus bypassing the problem caused by Notes agents all coming from the same user (the Notes server ID).

Everything in Lotus Notes, even code, is in documents which require access control list (ACL) controls on access. Consequently, the preferred embodiment of the invention uses Notes ACLs to access code. However, when accessing data, a role table 420 (see Figure 19) is used to build roles and permissions, and an object model is provided to generically access data from database 210, thus extending Notes to access a non-Notes data source 210. In order to configure DB2 to work in a Notes application environment, a single sign off is provided after getting through Notes code ACLs. This does not involve use of any of DB2's role tables and grants, but rather a single web ID 434 known to the Notes code to access the DB2 data.

Referring to Figure 19, role table 420 includes for each of a plurality of user WEB ID's 422, the associated role 424 and level 426 of granularity at which the user is

associated with the role. Example: for a role 424 of country administrator, the level 426 is the country id, and user with web ID 422 of 02 can update contract profiles for that country.

5 Any person at a browser 100 attempting to access a row in a DB2 table 390 must pass the role table 420 check. Further, for accessing a supplier table in DB2 390, anyone can view the list of suppliers in the application that applies to the requesters country, but only the country administrator can update them.

10 User 422 identifies a user profile 430, which specifies the user name 432, web identifier 434, charge information 436, including country, company, work location) and delivery information 438 (including street, office, and building).

15 Thus, in accordance with the preferred embodiment of the invention, the web ID 434 for the browser user is used to control access to the Notes databases and to the DB2 databases. The Notes databases have code and documents which the user must access (including contract profiles, cost center profiles) and also tables in the DB2 database. A user must access both Notes databases and DB2 databases, and access to all of these databases is controlled based on

the user web ID 434 through the use of role table 420.

In order to make and use the preferred embodiment of the invention, an implementer and user would do the following:

- 5 1. Determine what levels of granularity are relevant to the application. (For example, the company that the user belongs to, the country, etc.)
2. Populate the DB2 table 420 with Web IDs 434 and associated roles 424 and levels 426.
- 10 3. Write procedures to locate a user 422 in table 420 and pull out associated roles 424 and levels 426.
4. Provide code routines or functions using these procedures which are authorized for execution by users with specific roles and levels.
- 15 Code using these routines would then compare the roles and levels to the specific role and level that is required based on the function. For example, a user could be defined as a country administrator for France and a company administrator for a small company in the US. A routine that updates

accounting information for the small company would not care about the country-level authority, so would look in role table 420 for company administrator role 424 for this user web ID 422. The level 426 of the role 424 would further restrict this user 422 from updating the accounting information for any company in the US other than the one corresponding to the level 426 to which he is assigned.

The invention allows a person's access to DB2 tables to be limited by the contents of a second db2 table rather than the grants issued by the DBA. In the Notes environment of the preferred embodiment of the invention, the ID which is actually granted the authority to the table is the Notes Server machine since the server accessing the db2 tables is the Notes server. Since the user web id is once removed, this provides a mechanism for applying a level of authority to the user to then apply to the db2 table. That mechanism is the role table.

Table 4 lists and describes the Req/Cat Web tables of the preferred embodiment of the invention.

TABLE 4 REC/CAT WEB ADMINISTRATION TABLES

ADMINISTRATION FUNCTION	TABLE	DESCRIPTION
Access Authority	REQCAT.TROLE_AUTHORITY	Maps a user to a role and the qualifier for that role (i.e., what level)
	REQCAT.TROLE_CODE	Defines the list of valid roles - Global Admin, Country Admin, etc
Account numbers	REQCAT.TACCOUNT_PROFILE REQCAT.TLACCOUNT_PROFILE	Holds account codes to be validated against
	REQCAT.TACCT_PROF_DETAIL REQCAT.TLACCT_PROF_DETAIL	Provides details about the account codes
	REQCAT.TACCT_VALIDATION1	Holds account codes to be validated against, as well as what type of validation is occurring (i.e., against BMS, Remind, Project numbers, Customer numbers, etc)
	REQCAT.TACCT_VALID_TYPE	Defines the list of validation types
	REQCAT.TCOMP_COA REQCAT.TLCOMP_COA	Defines the GL account numbers that are available for each company code, and provides a translated description
Approver routing	REQCAT.TAPPROVER_ASSIGN	Links an approver to a type and a code (i.e. I/T 0001)
	REQCAT.TAPPROVER_PROFILE	Defines the approver's name, Web ID, etc.
	REQCAT.TAPPRV_TYPE_PROF	Defines the types of approvers available to the application (capital, financial, I/T, chemical, safety, tax)

ADMINISTRATION FUNCTION	TABLE	DESCRIPTION
	REQCAT.TCATLG_APPROVAL	Allows a catalog administrator to flag a catalog item as requiring chemical or safety approval in specific locations. For example, toner is not considered a chemical item except in Vermont, because of special environmental laws in that state.
Buyer routing	REQCAT.TBUYER_PROFILE	Defines the owner of a buyer code and contact information
	REQCAT.TBUYER_ROUTING	Links a buyer to a commodity
	REQCAT.TBUYER_SUPPLIER	Links a buyer to a supplier
Catalog profiles	RC.CATALOG	Defines the characteristics of a catalog - supplier, expiration date, currency, etc.
	RC.CATPLREL	Defines the plants which are allowed to access this catalog
Commodity families	NC.CATEGORY	Defines the global list of commodity groupings
Commodity codes	RC.COMMOCODE	Defines the global list of commodities and identifies which family each belongs to
Company commodities	RC.COMMCOMP	Not all commodities may be valid for all companies. This table identifies which commodity codes the company wants to use.
	REQCAT.TCOMMCOMP_BUYER	Some commodities require that the user select a buyer from a predefined list. This is the predefined list.
	REQCAT.TCOMM_COMP_COA	This associates GL account codes with the commodity code.

ADMINISTRATION FUNCTION	TABLE	DESCRIPTION
	REQCAT.TCOMM_WLOC_RCV	This defines for which work locations this commodity is 'receivable'. This flag is forwarded to SAP for further use in receiving locations
	RC.SUBCOMMODITY	Some commodities are too broad and the need exists for sub-dividing the goods under this commodity so that different suppliers and different purchase processes can be used.
	RC.SUPPSUBCOMM	This links a supplier to a specific subcommodity.
Companies	RC.COMPANY	Associates SAP company codes with associated country. For example, IBM US contains three company codes for IBM, Lotus, and Tivoli.
Countries	RC.COUNTRY	Holds the list of ISO country codes, i.e., US, FR, DE, etc
Company groups	REQCAT.TCOMPGRP_TYP_PROF	Defines the list of valid grouping types, such as ACCOUNT, UPROF
	REQCAT.TCOMPGRP_PROFILE	Defines the list of group names and links them to their types, such as IBMUS - ACCOUNT and IBMUS - UPROF
	REQCAT.TCOMPANY_GROUPING	Lists the company codes that belong to the specified grouping
Plants	RC.PLANT	Associates plant codes with company and country. A company can have many plants, a plant may belong to only one company.
Suppliers	RC.SUPPLIER	Defines the characteristics of a supplier - name, code, contact information, location

ADMINISTRATION FUNCTION	TABLE	DESCRIPTION
	RC.SUPPCOMP	Defines which company codes may reference this supplier for purchasing
Work locations	REQCAT.TWORK_LOCATION REQCAT.TLWORK_LOCATION	Associates work locations with plant, company, and country. A plant can have one or more work locations, a work location may belong to only one plant.
	REQCAT.TWORKLOC_DELTOADDR	For those work locations which have a predefined CDC (Chemical Delivery Center) address
User profiles	REQCAT.EMPLOYEE_PROFILE	Holds employee information
Catalog parts	see Figure 18, DB2 NCF tables 368	Hold part information, category / subcategory information, etc.

6. Relational DB Agents

In accordance with a preferred embodiment of the invention, in a Notes/DB2 hybrid environment, a Notes agent reads data from a DB2 table, and then dynamically populates that data to an HTML page. In this manner, an the existing infrastructure (including Notes, Domino Go, and DB2) is used to combine HTML and Java script web presentation with DB2 data.

Referring to Figure 20, Notes agents 440 are used as intermediaries. Each such agent 440 reads DB2 tables 390, collects data using SQL select statements, and builds web page 442 dynamically, writing out the Java script and HTML to present the page on a Web browser, such as Web browser 100. The results of the DB2 searches also helps to determine which HTML needs to be written, something which standard HTML cannot handle. Thus, conditional logic may be used.

A plurality of agents 440 are provided. The premise is the same in all: figure out who is asking, and then tailor what is shown by what they are authorized to see. The example of Table YY is the supplier profile agent.

This process makes use of the Notes connection function lsx:lc. This Lotus Script connection is a built in API for connectivity to relational databases. The lsx:lc connector is a Lotus provided API which allows connection to DB2.

For example, to display a list of supplier profiles, two DB2 tables 390 must be read: one provides a list of suppliers and the other is role table 420 (Figure 19). When role table 420 is read, the code tests the users ability to edit (country admin for country of supplier), and may

display the web page differently depending thereon. A dynamic feature of the invention is that straight text may be displayed, or with text with hyperlinks to open a supplier profile, as an example.

5 To make and use this preferred embodiment of the invention, the following is done:

1. Use the Lotus Script lsx:lc connector connect to DB2.
2. Depending on the DB2 table being read and the functions required, write functions to Create, Read, Update, and
10 Delete with respect to the DB2 table.
3. Write the HTML to display the page, and then have the Notes agent 440 Print these HTML commands to the browser so that they appear in a meaningful presentation to the end user.
- 15 4. Use conditional logic to change the look of the page 442 based on the results of the DB2 390 lookups.

Inputs to the method of this embodiment of the invention include the DB2 table to be read or updated, and the output includes HTML conditionally generated based on

results of the DB2 table reads.

The HTML page being populated may, for example, provide a list of suppliers. Such pages may also be used in the requisition or configuration area of the application, displaying commodity codes, suppliers, and so forth.

TABLE 5 EXAMPLE AGENT 440

```
1  This agent is invoked from the administration tab for 'supplier'. It is
2  presenting the user with a view of suppliers that have been configured
3  on the system. Based on the access authority of the user, this list
4  will be presented either as just text, for the general user, or as
5  hotlinks for an administrator to then open an individual supplier
6  profile and update it.

7  Sub Initialize
8  //setting up variables
9      Dim src As New LCConnection ("db2")
10     Dim fldLst As New LCFieldList(100)
11     Dim suppname As LCField
12     Dim suppcode As LCField
13     Dim InfoView As AllInfoView
14     Dim session As New NotesSession
15     Dim doc As NotesDocument
16     Dim sqlQueryString As String
17     Dim flag As Variant
18     Dim admin As Integer
19     Admin=True
20     Dim lclsxSession As LCSession
21     Dim supplierdb As notesdatabase
22     Dim configview As notesview
23     Dim configdoc As notesdocument
24     Dim lookuptype As String
25
26     On Error Goto errHandler
27
28     Set supplierdb=session.currentdatabase
29     Set configview = supplierdb.getview("APPVIEW")
30     Set configdoc = configview.getfirstdocument
31     lookuptype = configdoc.HRFormat(0)
32
33     Set doc=session.DocumentContext
34     Set InfoView=New AllInfoView
35
36     //connect to DB2
```



```

86      './SUPPLIER?OpenForm';"" >"
87          Print "</form>"
88      Else
89          Print "<BR>"
90      End If
91
92      Print "<table cellpadding=2 cellspacing=0 border=0>"
93      Print "<tr><td class=""bannersublevel"" ><B> Supplier</B></td>"
94      Print "</tr>"
95
96      //Toggling background color on alternate rows
97
98      flag = True
99
100     While (src.Fetch (fldLst) > 0)
101         If (flag) Then
102             Print "<tr bgcolor=#CCCCCC>"
103             flag = False
104         Else
105             Print "<tr bgcolor=#FFFFFF>"
106             flag = True
107         End If
108
109         //If user is an admin, then print the supplier name as a hotlink
110
111         If Admin Then
112             Print"<td class=""field""> <a href=./SUPPLIER?OpenForm&"
113             & suppcode.text(0) & ">"&suppname.text(0)&"</a> </td>"
114             Else
115
116             //otherwise just print it as text
117
118             Print"<td class=""field"">" &suppname.text(0)&"</td>"
119             End If
120             Print"<td class=""field"">" &suppcode.text(0)&"</td>"
121             Print "</tr>"
122         Wend
123         Print "</table>"
124     End
125
126     errorHandler:
127
128     Print "<br>" & session.currentagent.name & " - Line # " &Str(Erl)
129     & " // Error " & Str(Err) & ": " & Error$
130     If (lclsxSession.Status <> LCSUCCESS) Then
131         Dim text As String
132         Dim extcode As Long
133         Dim exttext As String
134
135         Call lclsxSession.GetStatus (text, extcode, exttext)
136         If (lclsxSession.Status = LCFAIL_EXTERNAL)Then
137             Print "<br>DB2 message: " & exttext & " code #" &
138             Cstr(extcode)
139         Else
140             Print "<br>Connector message: " & text
141         End If
142     Else

```


139 Print Error\$
140 End If
141
142
143 End Sub

7. Data Transfer

In accordance with the preferred embodiment of the invention, a system and method is provided for transferring to a Req/Cat Web (RCW) application in a timely manner large quantities of data from web sites that exist outside of a
5 firewall, or internal applications within the firewall but outside of the Req/Cat Web application.

For the purpose of the description of this embodiment, RCW exists in a frame set in a browser. A frame set divides
10 a screen into logical and user-friendly sections called frames. As part of security for browser 100, Netscape and Internet Explorer (IE) establish ownership of the frames: each frame is a window under control of browser 100. Browser 100 can open up a session in any frame desired.
15 However, if all of the frames open on a browser are not owned by same session, then these frames cannot see the contents of each other.

Consequently, the problem is presented: if RCW needs to

access an outside supplier site 300 for information to get
back through one its own the frames, as soon as data is
written by that other site into one of the frame at browser
100, RCW no longer owns the frame and cannot access the
5 information. So this aspect of the invention is concerned
with data passing.

In accordance with the preferred embodiment of the
invention, the supplier 300 opens a new window through
normal Java script commands and writes its data into it,
10 along with the name of the agent to run in RCW application
server 114. That new window then calls one of the RCW
processes, which is able to see the data because it is not
in a frame and is therefore available for RCW to access.
That process causes an agent to runs (in RCW) that can see
15 that data and write it to a frame on the RCW side, resulting
in RCW owning both the data and the frame. This allows RCW
to reach NOTES information, and write that information to
other frames. RCW owns the data and the frame. Ownership
is established in the RCW application.

20 Consequently, by carefully tracking and controlling the
sequence of opening windows, RCW can establish the origin
from which data is coming, where the data is going, and
which process owns it.

Those are the high points. Review: two sites are talking to each other using an intermediate window, doing a handoff of data and of ownership of both data and frame such that when it is time to supply information to the RCW application, RCW owns the data, frame and process.

Referring to Figure 21, a system and method are provided for data transfer from a externally owned site to an application owned frame set which operates as follows. The RCW application opens a supplier site URL in a temporary frame 456. Upon user selection of go to supplier 451, as is represented by step 458, frame 456 opens the supplier window 460 as a separate browser session. Two windows are now open: the original application 450 with its window underlying, and a supplier window 460 over it with the supplier URL. The reason for doing this is that the supplier requires that the browser be full frame, not in a small frame set. The primary RCW application in window 450 is quiesced to a wait state. As is represented by steps 462, the user can now select from window 460 items to buy, search, or whatever the supplier deems is appropriate for a user to order his data. The user then issues the command to submit the order. In step 444, the supplier site then gathers content from order data entered at window 460, in step 446 formats the page, and in step 448 issues a call to

Req/Cat Web to open third window 464 with first agent 480.
The supplier uses an enterprise specified agent name for
first agent 480 when opening third window 464. Third window
464 is a window, but not a frame, and thus the Req/Cat Web
5 can get access to it even though it is opened by the
supplier. First agent 480 includes an html form command 488
which defines the processing to be done on the contents 466
of the form now displayed in third window 464, and the
supplier site writes into this third window 464 unique order
10 identifying information. Once written, the browser
activates the form. Once activated, it is a program in its
own right, the html 488 that was written and any java script
in it will execute. One of first things it does is look at
the action in the form command and determine that this is
15 the program that will run to deal with the contents of this
form. That action program, or first agent 480, is a RCW
action program on the RCW server that can see contents of
third window 464 because it is not in a frame, and thus
ownership is not critical. In step 482, first RCW agent 480
20 executes a program or process that writes the contents 466
of window 464 back into its frame set (temporary frame) 456,
and then calls second agent 484 which references Java script
code 454 and, as is represented by step 486, access Notes
data on the Notes server, add content to the requisition,
25 and issue the commands that send the order to be stored in

the requisition. This is key, Req/Cat Web has used its own process 480 to write into its own window 450, and knows who owns the data. First agent 480 process opened window 464 and writes the data to temporary frame 456 and then kicks off another process, second agent 484, that can read that data, can read and write to all of the frames 452 in the application, can access information from Lotus notes, and write all the information into the requisition.

Window 460 is provided by a supplier site from outside the application, and possibly also outside a firewall. Window 460 is an external application that allows execution of code 462 for performing search, select, submit (call enterprise server, which may be inside firewall), and order data, including gather content 444, formatting the page 446, and calling RCW 448 with the first agent 480 as an action form.

Window 464 is a window opened by the supplier to include a Req/Cat Web agent, first agent 480. First agent 480 posts document contents to temporary data frame 456. As a variation, for skills matching, calls are made to the agents 480, 484 with a parameter after placing the data to retrieve in a Notes database. The second agent 484 retrieves the data, can look up and add supporting data from

yet another Notes database.

The key consideration here is, "who owns the frame".
The server that owns the agent that last wrote a frame owns
it, and can see its content, but cannot see any other
5 frame's contents if they were written by another server's
programs or agents.

Window 464 and first agent 480 act as an intermediary.
Content 466 is owned by the supplier server 300, but the
first agent 480 is owned by the Req/Cat Web server 114.
10 That first agent 480 then kicks off the rest of the process,
passing the data and ownership to the RCW server 114 and the
second agent 484. The second agent 484 can now can access
Notes data on the Notes server 112, and issue the commands
that send the order to be stored in the requisition.

15 8. Customizable Side Bar

In accordance with the preferred embodiment of the
invention, a customizable side bar is provided. Dynamic
HTML is used by the navigator responsive to user input to
change data presented at the screen without having to

communicate with a remote server.

Referring to Figure 4, navigation frame or menu bar appears, typically, on the left of a display window, to display a plurality of menu boxes, including headers 491-494 and items 495-500. As a cursor is moved over the headers, each individual header is highlighted or some symbol 481, 483, 485, 487, respectively, rotated by, say, 45 degrees, so as to point either down or to the right, to indicate to the user the header which will, upon being clicked, toggled to either a collapsed or expanded state from its current expanded or collapsed state, respectively. As illustrated, headers 481 and 483 are in a collapsed state, and headers 485 and 487 are in an expanded state. When expanded, header 485 is expanded to show items 495-498, and header 487 to show items 499-500. The user may move the cursor to one of items 495-500, and select the item to update the data displayed in content frame 480.

Heretofore, when the user selects (clicks on) a menu header 491, there is generally a pause as the request is made to the server to obtain a new page including an expanded menu bar 472 including a display of the included items. In accordance with a preferred embodiment of the invention, when server loads the window to a client, all of

the information required to load the menu bar 472 is provided, including information for the expanded menu items (but not the content frame associated with them). If a menu header 485 is clicked when in the collapsed state, the menu items 496-498 are shown or made visible and the following menu headers and items are moved relative to the expanded menu bar. If a menu item 496 is clicked, then communication with the server is required to load the content frame 480.

Upon initial load, all headers 491-494 are collapsed and all menu items are hidden. Menu headers 491-494 are displayed below each other with no gaps between them. Clicking on a last menu header merely shows all the menu items and moves nothing below it. Clicking on the first menu header would show all of its items and move every header and item a constant amount without changing its visibility state. (The display area 472 may be off of the window, but is available via the scroll bar 490.) In accordance with this embodiment of the invention, the result of selecting a header 491-494 is an instantaneous response from the client browser either expanding or collapsing the selected header and respectively displaying or removing from display the included items.

This is done using dynamic html (dhtml), which allows

creation of divisions within a document. These divisions are equivalent to tab items, menu items 495-500, or headers 491-494. In Netscape, these divisions are called layers. In Explorer, the layers are called divisions. These divisions can be hidden or shown, and moved relative distances on the screen. The current state of the art is to use these divisions for moving or flashing graphics, but not for business applications such as menu bars. In accordance with the present invention dhtml at the client creates subtle changes, business like, in the menu bar 472 without requiring server communications. The use of dhtml is described at developer.netscape.com.

Java script code, executable at a client for inserting, showing, moving and updating a menu bar 472, is illustrated in Table 6.

TABLE 6 MENU BAR CODE

```
1  ---- JavaScript (appNav.js)  ----
2  // appNav Class Constructor
3  -----
4  // This class implements a JavaScript Object intended to represent the
5  Navigator function   appNav(menuVar)  {
6
7      //methods
8      this.init = appNavInit;
9      this.sizeit = appNavSizeit;
10     this.toggleText = appNavToggleText;
11     this.isItem = appNavIsItem;
12     this.reverse = appNavReverse;
13
14     // properties
```

```

13      this.ns = document.layers;
14      this.ie = document.all;

15      this.loaded = 0;
16      this.whichone = 0;
17      this.whichgroup = 0;
18      if ( this.ns ) {
19          this.show = 'show';
20          this.hide = 'hide';
21      } else {
22          this.show = 'visible';
23          this.hide = 'hidden';
24      }
25      this.menus = menuVar;
26      this.max = menuVar.length;
27      this.images = new Array(this.max);
28      this.menuMove = new Array(this.max);
29      for (i=0;i < this.max; i++) this.menuMove[i] = 20 * (menuVar[i] -
30 1);
31      this.tabShow = [false, false, false, false, false, false, false,
32 false];
33  }

34  function appNavInit() {
35      var k=0;
36      if (this.loaded == 0) {
37          for (i=0; i < this.menuMove.length; i++) {
38              this.images[i] = new Array(this.menus[i]);
39              for (j=0; j < this.menus[i]; j++) {
40                  this.images[i][j] = new Image();
41                  pos = ("0"+i).slice(i>9,2) + ("0"+j).slice(j>9);
42                  this.images[i][j].src = "../images/men" + pos
43  + ".gif"
44                      if (this.ie) {
45
46 document.images[k].src=this.images[i][j].src;
47                     k++;
48                     } else
49
50 document.layers["D"+pos].document.images[0].src=this.images[i][j].src;
51                     }
52                 }
53                 this.loaded=1;
54             }
55         };

56  function appNavSizeit() {
57      if (this.loaded==1) {this.loaded = 0; this.init();}
58  };

59  function appNavToggleText(z) {
60      if (this.loaded==1) {
61          this.tabShow[z] = !this.tabShow[z]
62          for (j=1; j<this.menus[z]; j++) {
63              pos = ("0"+z).slice(z>9) + ("0"+j).slice(j>9);
64              if (this.ie)
65                  text = document.all("D"+pos).style

```



```

119 href="javascript:top.jsCode.validateInitiator(top.DBCreateReq+'/WebReq?O
120 penForm&RFQ',top.reqData)">
121 <img alt="New RFQ" width=125 height=20 border=0></a></div>
122 <div ID=D0003 style="top:80px;">
123 <a
124 href="javascript:top.jsCode.validateInitiator(top.DBCreateReq+'/WVRDraft
125 s?OpenView',top.content)">
126 <img alt="From Draft" width=125 height=20 border=0></a></div>
127 <div ID=D0004 style="top:100px;">
128 <a
129 href="javascript:top.jsCode.validateInitiator(top.DBCreateReq+'/WVRCRRej
130 ected?OpenView',top.content)">
131 <img alt="From Rejected Reqs" width=125 height=20
132 border=0></a></div>
133 <div ID=D0005 style="top:120px;">
134 <a
135 href="javascript:top.jsCode.validateInitiator(top.DBCreateReq+'/Template
136 s?OpenView',top.content)">
137 <img alt="From Template" width=125 height=20 border=0></a></div>
138 <div ID=D0006 style="top:140px;">
139 <a
140 href="javascript:top.jsCode.validateInitiator(top.DBCreateReq+'/WVRCRRFQ
141 ?OpenView',top.content)">
142 <img alt="From Complete RFQ" width=125 height=20
143 border=0></a></div>
144 <div ID=D0100 style="top:40px; visibility:show; visibility:visible;">
145 <a href="#" onClick="myNav.toggleText(1); return false;">
146 <img alt="View Requisitions" width=125 height=40
147 border=0></a></div>
148 <div ID=D0101 style="top:80px;">
149 <a
150 href="Javascript:top.jsCode.tocontent(top.DBCreateReq+'/WVRInProcess?Ope
151 nView')">
152 <img alt="In Process" width=125 height=20 border=0></a></div>
153 <div ID=D0102 style="top:100px;">
154 <a
155 href="Javascript:top.jsCode.tocontent(top.DBOpenReq+'/WVRSentToProcureme
156 nt?OpenView')">
157 <img alt="Sent To Procurement" width=125 height=20
158 border=0></a></div>
159 <div ID=D0103 style="top:120px;">
160 <a
161 href="Javascript:top.jsCode.tocontent(top.DBCreateReq+'/WVRInactive?Open
162 View')">
163 <img alt="Inactive" width=125 height=20 border=0></a></div>
164 <div ID=D0104 style="top:140px;">
165 <a
166 href="Javascript:top.jsCode.tocontent(top.DBPaidReq+'/WVRPartiallyPaid?O
167 penView')">
168 <img alt="Partially Paid" width=125 height=20 border=0></a></div>
169 <div ID=D0105 style="top:160px;">
170 <a
171 href="Javascript:top.jsCode.tocontent(top.DBArchive+'/WVRArchived?OpenVi
172 ew')">
173 <img alt="Archived" width=125 height=20 border=0></a></div>
174 <div ID=D0200 style="top:80px; visibility:show; visibility:visible;">
175 <a href="#" onClick="myNav.toggleText(2); return false;">

```

```

176         <img alt="For Approvers Only" width=125 height=40
177 border=0></a></div>
178 <div ID=D0201 style="top:120px;">
179     <a
180 href="Javascript:top.jsCode.tocontent(top.DBCreateReq+'/WVFAOAwaitingApp
181 roval?OpenView')">
182         <img alt="Awaiting Approval" width=125 height=20
183 border=0></a></div>
184 <div ID=D0202 style="top:140px;">
185     <a
186 href="Javascript:top.jsCode.tocontent(top.DBCreateReq+'/WVFAOApprovedByM
187 e?OpenView')">
188         <img alt="Approved by me" width=125 height=20 border=0></a></div>
189 <div ID=D0203 style="top:160px;">
190     <a
191 href="Javascript:top.jsCode.tocontent(top.DBCreateReq+'/WVFAORejectedByM
192 e?OpenView')">
193         <img alt="Rejected by me" width=125 height=20 border=0></a></div>
194 <div ID=D0300 style="top:120px; visibility:show; visibility:visible;">
195     <a href="#" onClick="myNav.toggletext(3); return false;">
196         <img alt="Users" width=125 height=20 border=0></a></div>
197 <div ID=D0301 style="top:140px;">
198     <a
199 href="javascript:top.jsCode.tocontent(top.DBCreateReq+'/WebUser'+top.app
200 Owner+'?OpenForm&MINE'+&''+top.jsCode.companygroupcode);">
201         <img alt="My Profile" width=125 height=20 border=0></a></div>
202 <div ID=D0302 style="top:160px;">
203     <a
204 href="javascript:top.jsCode.tocontent(top.DBCreateReq+'/WebUserSearch?Op
205 enForm&SRCH'+top.jsCode.companygroupcode);">
206         <img alt="Search Profiles" width=125 height=20 border=0></a></div>
207 <div ID=D0400 style="top:140px; visibility:show; visibility:visible;">
208     <a href="#" onClick="myNav.toggletext(4);return false;">
209         <img alt="Administration" width=125 height=20 border=0></a></div>
210 <div ID=D0401 style="top:160px;">
211     <a
212 href="Javascript:top.jsCode.tocontent(top.DBCfg+'/AgentRunner?OpenForm&g
213 etIDs&')">
214         <img alt="Access Authority" width=125 height=20
215 border=0></a></div>
216 <div ID=D0402 style="top:180px;">
217     <a
218 href="Javascript:top.jsCode.tocontent(top.DBCfg+'/AgentRunner?OpenForm&V
219 iewAccounts')">
220         <img alt="Account Numbers" width=125 height=20 border=0></a></div>
221 <div ID=D0403 style="top:200px;">
222     <a
223 href="Javascript:top.jsCode.tocontent(top.DBCfg+'/AgentRunner?OpenForm&V
224 iewBuyerInfo')">
225         <img alt="Buyer Information" width=125 height=20
226 border=0></a></div>
227 <div ID=D0404 style="top:220px;">
228     <a
229 href="Javascript:top.jsCode.tocontent(top.DBCfg+'/AgentRunner?OpenForm&V
230 iewBuyerRouting')">
231         <img alt="Buyer Routing" width=125 height=20 border=0></a></div>
232 <div ID=D0405 style="top:240px;">

```

```

233         <a
234 href="Javascript:top.jsCode.tocontent(top.DBCfg+'/WBUSINESSENTITIES?Open
235 View')">
236         <img alt="Business Units" width=125 height=20 border=0></a></div>
237 <div ID=D0406 style="top:260px;">
238         <a
239 href="Javascript:top.jsCode.tocontent(top.DBCfg+'/WCAPITALAPPROVERS?Open
240 View')">
241         <img alt="Capital Approvers" width=125 height=20
242 border=0></a></div>
243 <div ID=D0407 style="top:280px;">
244         <a
245 href="Javascript:top.jsCode.tocontent(top.DBCfg+'/AgentRunner?OpenForm&V
246 iewCatalog&')">
247         <img alt="Catalogs" width=125 height=20 border=0></a></div>
248 <div ID=D0408 style="top:300px;">
249         <a
250 href="Javascript:top.jsCode.tocontent(top.DBCfg+'/WCHEMICALAPPROVERS?Ope
251 nView')">
252         <img alt="Chemical Approvers" width=125 height=20
253 border=0></a></div>
254 <div ID=D0409 style="top:320px;">
255         <a
256 href="Javascript:top.jsCode.tocontent(top.DBCfg+'/AgentRunner?OpenForm&V
257 iewCommCode&')">
258         <img alt="Commodity Codes" width=125 height=20 border=0></a></div>
259 <div ID=D0410 style="top:340px;">
260         <a
261 href="Javascript:top.jsCode.tocontent(top.DBCfg+'/AgentRunner?OpenForm&V
262 iewCommFam')">
263         <img alt="Commodity Families" width=125 height=20
264 border=0></a></div>
265 <div ID=D0411 style="top:360px;">
266         <a
267 href="Javascript:top.jsCode.tocontent(top.DBCfg+'/WCOMPANIES?OpenView') "
268 >
269         <img alt="Companies" width=125 height=20 border=0></a></div>
270 <div ID=D0412 style="top:380px;">
271         <a
272 href="Javascript:top.jsCode.tocontent(top.DBCfg+'/WCOMPCOMMODS?OpenView'
273 )">
274         <img alt="Company Commodities" width=125 height=20
275 border=0></a></div>
276 <div ID=D0413 style="top:400px;">
277         <a
278 href="Javascript:top.jsCode.tocontent(top.DBCfg+'/WCONTRACTS?OpenView') "
279 >
280         <img alt="Contracts" width=125 height=20 border=0></a></div>
281 <div ID=D0414 style="top:420px;">
282         <a
283 href="Javascript:top.jsCode.tocontent(top.DBCostCtr+'/WCOSTCENTERS?OpenV
284 iew')">
285         <img alt="Cost Centers" width=125 height=20 border=0></a></div>
286 <div ID=D0415 style="top:440px;">
287         <a
288 href="Javascript:top.jsCode.tocontent(top.DBCfg+'/WCOUNTRIES?OpenView') "
289 >

```


5 under the second group). Netscape recognizes the div tags
as layers. Internet Explorer recognizes them as layers.

Advantages over the Prior Art

10 It is an advantage of the invention that there is
provided a scalable database system in a web environment
with optimal access performance characteristics for an
expanding number of clients and a growing database.

15 It is an advantage of the invention that there is
provided a system and method for enabling a requester to
select the correct general ledger account when doing
financial validation on a requisition.

20 It is an advantage of the invention that there is
provided a system and method for utilizing Lotus script
extensions in combination with a relational database to
provide high capacity storage without performance
degradation.

It is an advantage of the invention that there is provided a system and method for enabling a buyer a means for editing catalog content before externalizing it to production for access by requesters.

25 It is an advantage of the invention that there is provided a system and method for providing very flexible access to DB2 tables without requiring database administrator (DBA) involvement to issue grants against the tables, and bypassing the problem caused by Notes agents all
30 coming from the same user (the Notes server ID).

It is an advantage of the invention that there is provided a system and method utilizing an existing infrastructure including Lotus Notes, Domino Go, and DB2 to combine HTML and Java script web presentation with DB2 data.

35 It is an advantage of the invention that there is provided a system and method for enabling transfer of data from a supplier site to a RCW application which does not entail frame spoofing.

40 It is an advantage of the invention that there is provided a system and method for dramatically increasing the speed of operation of a navigation frame of a GUI.

Alternative Embodiments

It will be appreciated that, although specific
embodiments of the invention have been described herein for
purposes of illustration, various modifications may be made
without departing from the spirit and scope of the
invention. In particular, it is within the scope of the
invention to provide a computer program product or program
element, or a program storage or memory device such as a
solid or fluid transmission medium, magnetic or optical
wire, tape or disc, or the like, for storing signals
readable by a machine, for controlling the operation of a
computer according to the method of the invention and/or to
structure its components in accordance with the system of
the invention.

Further, each step of the method may be executed on any
general computer, such as an IBM System 390, AS/400, PC or
the like and pursuant to one or more, or a part of one or
more, program elements, modules or objects generated from
any programming language, such as C++, Java, Pl/1, Fortran
or the like. And still further, each said step, or a file
or object or the like implementing each said step, may be

executed by special purpose hardware or a circuit module
65 designed for that purpose.

Accordingly, the scope of protection of this invention
is limited only by the following claims and their
equivalents.

END9 2000 0111 US1

CLAIMS

We claim:

- 1 1. A navigation frame, comprising:
 - 2 a screen display including a customizable side bar; and
 - 3 dynamic HTML used by a navigator responsive to user
 - 4 input to change data presented at said screen in said
 - 5 side bar without having to communicate with a remote
 - 6 server.
- 1 2. A browser frame, comprising:
 - 2 a navigation frame;
 - 3 a content frame;
 - 4 said navigation frame including a plurality of header
 - 5 boxes;

6 responsive to user selection of an individual header
7 tab, executing dynamic html to selectively toggle said
8 individual header tab between expanded and unexpanded
9 modes, said expanded mode including the display of
10 included item tabs and said unexpanded mode not
11 including said display.

1 4. The method of claim 3, further comprising the step of:

2 defining each said tab as a dynamic HTML division
3 capable of being moved relative distances and
4 selectively displayed and hidden in said display.

1 5. The method of claim 4, further comprising the steps of:

2
3 upon initial load, displaying all header tabs collapsed
4 and all menu tabs hidden; and

5 responsive to selection of a target header tab,
6 selectively moving, displaying, and hiding said tab
7 with respect to other tabs in said navigation frame.

1 6. The method of claim 5, further comprising the step of:

2 responsive to selection of a target item tab,
3 communicating with a server to refresh a content frame
4 in said browser window.

1 7. A program storage device readable by a machine,
2 tangibly embodying a program of instructions executable by a
3 machine to perform method steps for presenting a navigation
4 frame in a browser window, said method steps comprising:

5 loading to said browser navigation frame header
6 information and item information for expanding
7 individual header tabs; and

8 responsive to user selection of an individual header
9 tab, executing dynamic html to selectively toggle said
10 individual header tab between expanded and unexpanded
11 modes, said expanded mode including the display of
12 included item tabs and said unexpanded mode not
13 including said display.

1 8. A program storage device readable by a machine,

CONFIDENTIAL

2 tangibly embodying a program of instructions executable by a
3 machine to perform method steps for presenting a navigation
4 frame in a browser window, said method steps comprising:

5 loading to said browser navigation frame header
6 information and item information for expanding
7 individual header tabs;

8 responsive to user selection of an individual header
9 tab, executing dynamic html to selectively toggle said
10 individual header tab between expanded and unexpanded
11 modes, said expanded mode including the display of
12 included item tabs and said unexpanded mode not
13 including said display;

14 defining each said tab as a dynamic HTML division
15 capable of being moved relative distances and
16 selectively displayed and hidden in said display.

17
18 upon initial load, displaying all header tabs collapsed
19 and all menu tabs hidden;

20 responsive to selection of a target header tab,
21 selectively moving, displaying, and hiding said tab
22 with respect to other tabs in said navigation frame;

23 and

24 responsive to selection of a target item tab,
25 communicating with a server to refresh a content frame
26 in said browser window.

1 9. A computer program product or computer program element
2 for executing method steps for presenting a navigation frame
3 in a browser window, said method steps comprising:

4 loading to said browser navigation frame header
5 information and item information for expanding
6 individual header tabs;

7 responsive to user selection of an individual header
8 tab, executing dynamic html to selectively toggle said
9 individual header tab between expanded and unexpanded
10 modes, said expanded mode including the display of
11 included item tabs and said unexpanded mode not
12 including said display;

13 defining each said tab as a dynamic HTML division
14 capable of being moved relative distances and
15 selectively displayed and hidden in said display;

**SYSTEM AND METHOD FOR PROVIDING AN APPLICATION NAVIGATOR
CLIENT MENU SIDE BAR**

Abstract of the Disclosure

5 A hybrid Notes/DB2 environment provides a requisition
catalog on the Web. Client browsers are connected to a GWA
infrastructure including a first network dispatcher and a
virtual cluster of Domino.Go servers. The network
dispatcher sprays out browser requests among configured
10 .nsf servers in virtual server cluster. Communications from
this virtual server cluster are, in turn, dispatched by a
second network dispatcher servers in a Domino cluster.
External objects, primarily for a GUI, are served in a .dfs
and include graphic files, Java files, HTML images and
15 net.data macros. The catalog is built from supplier
provided flat files. A front end is provided for business
logic and validation, as also is a relation database
backend. HTML forms are populated using relational database
agents. A role table is used for controlling access both to
20 Notes code and DB2 data. Large amounts of data is quickly
transferred using an intermediate agent and window.




FIG. 1




FIG. 2

FIG. 3

002060" 667 6660





FIG. 4






FIG. 6




FIG. 7







FIG. 8








FIG. 12

COOPER




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21

DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

Atty.Docket No. END9-2000-0111 US1

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name; I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

System and Method for Providing an Application Navigator Client Menu Side Bar

the specification of which (check one)

 X

is attached hereto.

_____ was filed on _____ as Application Serial No. _____ and was amended on _____.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, section 119 of any foreign application(s) for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s):

Number	Country	Daty/Month/Year	Priority Claimed
--------	---------	-----------------	------------------

I hereby claim the benefit under Title 35, United States Code, section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States applications in the manner provided by the first paragraph of Title 35, United States Code, section 112, I acknowledge the duty to disclose information material to the patentability of this application as defined in Title 37, Code of Federal Regulations, section 1.56 which occurred between the filing date of the prior application and the national or PCAT international filing date of this application:

Prior U.S. Applications:

Serial No.	Filing Date	Status
------------	-------------	--------

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

As a named inventor, I hereby appoint the following attorneys and/or agents to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: David L. Adour, Reg. No. 29,604; Lawrence R. Fraley, Reg. No. 26,885; John R. Pivnichny, Reg. No. 43,001; Arthur J. Samodovitz, Reg. No. 31,297; William H. Steinberg, Reg. No. 28,540; Christopher A. Hughes, Reg. No. 26,914; Edward A. Pennington, Reg. No. 32,588; John H. Hoel, Reg. No. 26,279; Joseph C. Redmond, Jr., Reg. No. 18,753; and Shelley M Beckstrand, Reg. No. 24,886.

Send all correspondence to: Shelley M Beckstrand, P.C.
Attorney at Law
314 Main Street
Owego, NY 13827

Direct telephone calls to: (607) 687-9913 [alt: (607) 755-3268]

Signature: _____

Date: 9/6/2000

Residence: Stanley B. Cason
1289 Rhodes Road, Johnson City, New York 13790
Citizenship: USA
Post Office Address: Same as residence